



Faculty of Manufacturing Engineering

**DRY SLIDING WEAR AND FRICTION BEHAVIOR OF SILICON
CARBIDE AND MULTI WALL CARBON NANOTUBES
REINFORCED MAGNESIUM MATRIX HYBRID COMPOSITES**

Tee Zhen Wei

Master of Science in Manufacturing Engineering

2015

**DRY SLIDING WEAR AND FRICTION BEHAVIOR OF SILICON CARBIDE
AND MULTI WALL CARBON NANOTUBES REINFORCED MAGNESIUM
MATRIX HYBRID COMPOSITES**

TEE ZHEN WEI

**A thesis submitted
in fulfilment of the requirements for the degree of Master of Science in Manufacturing
Engineering**

Faculty of Manufacturing Engineering

UNIVERSITI TEKNIKAL MALAYSIA MELAKA

2015

DECLARATION

I declare that this thesis entitled “Dry Sliding Wear and Friction Behavior of Silicon Carbide and Multi-Walled Carbon Nanotubes Reinforced Magnesium Matrix Hybrid Composites” is the result of my own research except as cited in the references. The thesis has not been accepted for any degree and is not concurrently submitted in candidature of any other degree.

Signature :

Name :

Date :

APPROVAL

I hereby declare that I have read this thesis and in my opinion this thesis is sufficient in terms of scope and quality for the award of Master of Science in Manufacturing Engineering.

Signature :

Name :

Date :

DEDICATION

I Humbly Dedicate to

My Beloved Father and Mother,
Tee Cheng Sum and
Khoo Swee Lan

&

All My Friends;
Who Have Bring Me

The Gairty, Encourage, Delight and Happiness in My life!

ABSTRACT

In order to optimize the functionality of magnesium, a modest attempt has been made to develop magnesium hybrid composites incorporating of synthesis micro and nano size fillers. Commercially pure magnesium (Mg) reinforced with (i) 10 wt.% micro-sized silicon carbide (SiC) particles (ii) combination of 10 wt.% micro-sized silicon carbide (SiC) particles and 1 wt.% multi-walled carbon nanotubes (MWCNTs), respectively, were synthesized via powder metallurgy route followed by hot extrusion. After the specimen preparation, microstructural characterization studies were conducted to determine the distribution of reinforcement, grain morphology, and presence of porosity by using Optical Microscope, Scanning Electron Microscope and Field Emission Scanning Electron Microscopy. Density and porosity measurements were carried out accordance with Archimedes' principle. Micro-Vickers Test was also carried out to investigate the hardness of material. The dry sliding tests were performed using a pin-on-disc tester against a grey cast iron counterbody under two applied normal loads (5, 10, 20, 40 N) with four sliding speeds (0.5, 1.5, 3.5, 4.5 m/s) corresponding to a constant sliding distance of 5000 m to identify the wear rate and coefficient of friction of magnesium composite. The morphology of the worn pin surfaces and collected wear debris were examined using Scanning Electron Microscope. Throughout this work, reasonably uniform distribution of SiC particulates and MWCNTs in magnesium matrix were observed. Low porosity (below 2.0 %) was obtained which indicated the suitability of the processing parameters. The Vickers hardness of all the hierarchical magnesium composite configurations are significantly higher than the pure magnesium. Wear rate for both unreinforced magnesium and its composite increased with increasing load but the incorporation of micro and nano size fillers reduced the wear rate of magnesium particularly at loads of 5, 10, 20 N. The sliding speed increment induced higher wear on magnesium composites. However, at the highest load of 40 N, a crossover in wear rate was observed with the increased in sliding speeds, i.e., at sliding speed of 1.5 m/s the wear rate of the composite higher than unreinforced magnesium, but the incorporation of SiC and MWCNTs shifts to minimize the wear rate at sliding speeds of 3.5 and 4.5 m/s respectively. There is a small reduction in the coefficient of friction for Mg/SiC/MWCNTs composite as compared to Mg/SiC particularly at low loads of 5, 10, 20 N as the sliding speed increased but the change of coefficient of friction among different materials become insignificant at high load of 40 N. Five wear mechanisms mostly operated in combination namely abrasion, adhesion, oxidation, delamination and plastic deformation have been observed in various sliding conditions. Such modify hybrid approach may bring significant implications on application particularly in automotive and aviation sectors. These would become as another material option to further improve the fuel efficiency as well as service life of components.

ABSTRAK

Bagi mengoptimumkan fungsi magnesium, satu percubaan telah dibuat untuk menghasilkan komposit hybrid magnesium yang bertetulang saiz mikro dan nano. Magnesium tulen (Mg) diperkukuhkan dengan (i) 10 wt.% silikon karbida (SiC) bersaiz mikro (ii) 10 wt.% silikon karbida (SiC) bersaiz mikro dan 1 wt.% tiub nano karbon berdinding ganda (MWCNTs), masing-masing, telah disintesis melalui kaedah metalurgi serbuk diikuti oleh penyemperitan panas. Selepas penyediaan spesimen, kajian pencirian mikrostruktur telah dijalankan untuk menentukan pengagihan tetulang, morfologi ira, dan kehadiran keliangan dengan menggunakan Mikroskop Optik, Pengimbasan Elektron Mikroskop dan Bidang Pelepasan Mengimbas Mikroskopi Elektron. Ketumpatan dan keliangan pengukuran telah dijalankan mengikut prinsip Archimedes. Ujian micro-Vickers juga telah dijalankan untuk mengkaji kekerasan bahan. Ujian haus pada keadaan kering telah dilakukan dengan menggunakan penguji pin terhadap besi tuang kelabu di bawah empat kenaan beban normal (5, 10, 20, 40 N) dengan empat kelajuan gelongsor (0.5, 1.5, 3.5, 4.5 m/s) dengan jarak yang tetap, 5000 m untuk mengenal pasti kadar haus dan pekali geseran komposit magnesium. Morfologi permukaan pin yang telah haus dan serpihan haus yang dipungut telah diperiksa menggunakan Pengimbasan Elektron Mikroskop. Dari kajian ini, taburan yang seragam zarah SiC dan MWCNTs di dalam matriks magnesium telah diperhatikan. Keliangan yang rendah (di bawah 2.0 %) yang telah diperolehi menunjukkan kesesuaian parameter pemprosesan. Kekerasan Vickers bagi hierarki konfigurasi komposit magnesium adalah jauh lebih tinggi daripada magnesium yang tulen. Kadar haus untuk kedua-dua magnesium tanpa tetulang dan komposit meningkat dengan peningkatan beban tetapi penambahan pengisi bersaiz mikro dan nano mengurangkan kadar haus magnesium terutamanya pada 5, 10, 20 N. Peningkatan kelajuan gelongsor menyebabkan kadar haus yang lebih tinggi pada komposit magnesium. Walau bagaimanapun, pada beban tertinggi 40 N, peralihan dalam kadar haus diperhatikan dengan peningkatan dalam kelajuan gelongsor; iaitu pada kelajuan 1.5 m/s kadar haus daripada komposit lebih tinggi daripada magnesium tanpa tetulang tergelincir, tetapi penambahan SiC dan MWCNTs mengurangkan kadar haus pada kelajuan gelongsor 3.5 dan 4.5 m/s masing-masing. Terdapat pengurangan kecil dalam pekali geseran Mg/SiC/MWCNTs komposit berbanding Mg/SiC terutamanya pada beban rendah 5, 10, 20 N dimana kelajuan gelongsor meningkat tetapi perubahan pekali geseran di antara bahan-bahan yang berbeza menjadi tidak ketara pada beban tertinggi 40 N. Lima mekanisme haus yang kebanyakannya beroperasi secara gabungan iaitu lelasan, rekatan, pengoksidaan, delaminasi dan ubah bentuk plastik telah diperhatikan dalam pelbagai keadaan gelongsor. Pengubahsuaian komposit hybrid magnesium ini boleh membawa implikasi yang besar ke atas aplikasi terutamanya dalam sektor automotif dan penerbangan. Ia akan menjadi salah satu pilihan bahan untuk meningkatkan lagi kecekapan bahan api dan juga hayat perkhidmatan komponen.

ACKNOWLEDGEMENTS

Thank to God for giving me a strength and good health condition to accomplish my master thesis as scheduled. With deep regards and profound respect, I wish to extend my sincere and earnest gratitude to my main supervisor Professor Dr. Qumrul Ahsan, for his priceless guidance, valuable advice, constructive criticism and patience throughout in this research work. He has been an illuminated guide, not just in addressing the issues of the present work, but also in teaching me how to deal with people. When I wandered, he gave accurate directions just like a faithful GPS. His scientific advice and helpful comments have contributed the most towards the completion of my thesis. I am also very thankful to my co-supervisor Puan Siti Rahmah for her precious time spent especially providing some of the tools and resources which were essential to the work reported in this dissertation. I have no hesitation to admit that without their knowledge, continued support and encouragement on my research activity, this thesis would not been same as presented here. I would like to acknowledge financial support for this project provided by Universiti Teknikal Malaysia Melaka (UTeM) under the grant number of PJP/2011/FKP (18A) /S907 and allowing me to use entire facilities available to complete my testing and studies. Special thanks are addressed to the laboratory technicians who are Mr. Jaafar, Mr. Safarizal, Mr. Mazlan, Mr. Mohd Farihan, Mr. Sarman, Mr. Mohd Raduan, Mr. Muhammad Azwan for their tremendous technical support and assistance during the execution of my experimental work. In particular, I would like to thank Mr. Azrul Syafiq

for helping me whenever and whatever I needed in the tribology lab. Valuable help in metallographic and worn surface examinations by Mr. Azhar Shah for SEM and EDX and Mr. Sanadi Subhi for FESEM are also deeply appreciated. My sincere thanks also extends to my friends and my seniors, especially Mrs. Chong Meng Mun, Mr. Mohd Zaidan, Mr. Alans Ng Guan Yao, Mrs. Nurul Hazliza for their friendship and help rendered. Together we shared endless discussions and managed to get the positive out of the difficulties during our research. Last but not least, I would like to pay my gratitude to my parents who have invested in me, both emotionally and financially for the entire duration of my study. Their love and belief in me lit my path in life and helped me strive to reach towards horizon and beyond.

TABLE OF CONTENTS

	PAGE
DECLARATION	
APPROVAL	
DEDICATION	
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	v
LIST OF TABLES	viii
LIST OF FIGURES	ix
LIST OF APPENDICES	xvi
LIST OF ABBREVIATIONS	xvii
LIST OF SYMBOLS	xx
LIST OF PUBLICATIONS	xxi
 CHAPTER	
1. INTRODUCTION	1
1.1 Background	1
1.2 Problem statements	4
1.3 Objective of study	6
1.4 Scope of study	6
1.5 Dissertation outline	7
 2. LITERATURE REVIEW	8
2.1 Composite	9
2.2 Metal matrix composites	9
2.3 Matrix materials for metal matrix composites	11
2.3.1 Titanium	12
2.3.2 Aluminum	12
2.3.3 Magnesium	13
2.4 Particulate reinforcements for magnesium matrix composites	15
2.4.1 Particulate silicon carbide	16
2.4.2 Carbon nanotubes	18
2.5 Processing techniques of particulate reinforced metal matrix composites	20
2.5.1 Liquid state processing of metal matrix composites	22
2.5.1.1 Stir casting	22
2.5.1.2 Infiltration processes	23
2.5.2 Solid state processing of metal matrix composites	24
2.5.2.1 Powder metallurgy	24
2.5.3 Extrusion of metal matrix composites	31
2.6 Hardness of particulate reinforced magnesium matrix composites	34
2.7 Tribology of particulate reinforced magnesium matrix composites	36
2.7.1 Friction	37

2.7.2	Wear	38
2.7.2.1	Abrasive wear	39
2.7.2.2	Adhesive wear	40
2.7.2.3	Oxidation wear	41
2.7.2.4	Fatigue wear	42
2.7.2.5	Melt wear	43
2.6.2.3	Summary of literatures of wear in magnesium metal matrix composites	43
3.	METHODOLOGY	47
3.0	Overview	47
3.1	Materials	48
3.1.1	Magnesium	49
3.1.2	Silicon carbide	49
3.1.3	Multiwalled carbon nanotubes	50
3.2	Equipments / instruments used	50
3.3	Characterization of raw materials	51
3.3.1	Particle size analyzer	51
3.4	Sample preparation	51
3.4.1	Primary processing	51
3.4.1.1	Composition	52
3.4.1.2	Mechanical mixing	53
3.4.1.3	Compaction of the powder mixing	57
3.4.1.4	Sintering	59
3.4.2	Secondary processing	60
3.4.2.1	Hot extrusion	61
3.4.2.2	Cutting	62
3.4.2.3	Grinding	62
3.4.2.4	Polishing	63
3.5	Physical characterization	63
3.5.1	Density and porosity measurement	63
3.6	Mechanical characterization	65
3.6.1	Microhardness test	65
3.6.2	Tribology test	68
3.6.3.1	Experimental matrix design	68
3.6.3.2	Wear mechanisms characterization	70
3.7	Metallographic characterization	70
3.7.1	Optical microscopy	71
3.7.2	Scanning electron microscope	71
3.7.3	Field emission scanning electron microscope	73
4.	RESULTS AND DISCUSSION	74
4.0	Overview	74
4.1	Powder characterisation	74
4.1.1	Magnesium particles	75
4.1.2	Silicon carbide particles	76
4.1.3	Multi-walled carbon nanotubes	77
4.2	Macrostructural characteristics	77

4.3	Microstructural characteristics	78
4.4	Density and porosity measurement	82
4.5	Microhardness measurement	85
4.6	Wear data presentation	88
4.6.1	Effects of load	88
4.6.2	Effects of sliding speed	88
4.6.3	Effects of reinforcement	91
4.6.4	Coefficient of friction	91
4.7	Wear mechanisms	93
4.7.1	Abrasive wear	94
4.7.2	Oxidation wear	98
4.7.3	Delamination wear	101
4.7.4	Adhesive wear	103
4.7.5	Melt wear	105
4.8	Summary of wear behaviour	108
5.	CONCLUSION AND RECOMMENDATIONS	112
5.1	Conclusion	112
5.2	Recommendation	114
	REFERENCES	115
	APPENDIX A	133
	APPENDIX B	137
	APPENDIX C1	138
	APPENDIX C2	139
	APPENDIX C3	140
	APPENDIX D1	141
	APPENDIX D2	142
	APPENDIX D3	143
	APPENDIX E	144

LIST OF TABLES

TABLE	TITLE	PAGE
2.1	Advantages of MMCs compared to PMCs and unreinforced matrix alloys	9
2.2	Typical reinforcement used in metal matrix composites (Chawla and Chawla, 2006)	10
2.3	Comparison of properties between Mg with other common matrix materials	14
2.4	List of particulates used as reinforcement for magnesium composite	16
2.5	Properties of commonly used reinforcement particulates (Kainer, 2006)	17
3.1	Description of composition for magnesium hybrid composites in a total formulated powder of 30g	52
3.2	Factors and levels selected for the pin on disc test	69
4.1	Density results	82
4.2	Porosity results	84
4.3	Results of vickers hardness measurements for different samples	85
4.4	Summary wear mechanisms for each sliding condition and pin material	110

LIST OF FIGURES

FIGURE	TITLE	PAGE
1.1	Sturctures of this dissertation	7
2.1	Schematic structures of (a) SWCNT and (b) MWCNT (Choudhary and Gupta., 2011)	18
2.2	Schematic diagram of processing methods of metal matrix composites (Evans et al., 2003)	21
2.3	Schematic diagram showing the stir casting setup (Gupta and Sharon, 2011)	22
2.4	(a) The experimental set-up of the spontaneous or pressureless infiltration where Mg infiltration in mixed with SiC and SiO ₂ powders (b) Gas pressure infiltration (c) Squeeze casting infiltration (Chawla and Chawla, 2006)	23
2.5	Movements of working parts and balls in a planetary mill (Datta, 2012)	25
2.6	Sequence of compaction (a) Die fill stage (b) Compaction (c) Part ejection (Angelo and Subramanian, 2008)	27
2.7	Schematic diagram of progress of sintering: (i) Particles in contact, (ii) Initial stage, (iii) Intermediate stage, (iv) Final sintered geometry (German, 1996)	28

2.8	Schematic diagram of hot extrusion, showing effect on grain structure (Friedrich and Mordike, 2006)	31
2.9	Csf/AZ91D composite workpieces by liquid-solid extrusion ($v=4$ mm/s) at different temperatures: (a) 400 °C; (b) 410 °C; (c) 420 °C (Qi et al., 2010)	33
2.10	Extrusion constant k for various materials as a function of temperature (Kalpakjian et al., 2001 as cited in Komander 2009)	34
2.11	Steps involved in indentation during vicker hardness test (Gadermayr et al., 2012)	35
2.12	Schematic diagram of (a) Two-body abrasion mechanism (b) Three-body abrasion mechanism (Adapted and modified from Stachowiak and Batchelor, 2001)	40
2.13	Schematic process of the formation of an adhesive transfer particle (Adapted and modified from Stachowiak and Batchelor, 2001)	40
2.14	Schematic representations of oxidation of metallic surfaces at high contact temperatures (Adapted and modified from Stachowiak and Batchelor, 2001)	41
2.15	Schematic illustration of the process of surface crack initiation and propagation (Adapted and modified from Stachowiak and Batchelor, 2001)	42
2.16	Schematic illustration of the formation of molten layer (Adapted and modified from Stachowiak and Batchelor, 2001)	43
3.1	Methodology process flow chart	48

3.2	Digital photograph of Insmart mini planetary ball mill (Ceramic lab, FKP, UTeM)	54
3.3	Digital photograph of formulated powder (89 wt.% Mg, 10 wt.% SiC, 1 wt.% MWCNTs) (a) Before mixing (b) After mixed for 1 hour (c) After mixed for 2 Hour	55
3.4	Digital photograph of tool steel die-punch arrangement in Instron universal testing machine, model load frames: 5584 (Fitting and fabrication lab, FKM, UTeM)	57
3.5	Digital photograph of green compact	58
3.6	Digital photograph of high temperature horizontal tubular furnace, model: TF70-1600 (Tribology lab, FKM, UTeM)	59
3.7	Experimental heating cycles with 10° C / min heating rate for sintering magnesium composite samples	60
3.8	Digital photograph of 150 Ton hydraulic press machine (Fabrication lab, FKP, UTeM)	61
3.9	Digital photograph of Mitutoyo Vickers hardness tester, model: HM-200 series (Material lab, FKP, UTeM)	65
3.10	Digital photograph of Ducom pin-on-disc tester, model: TR-20LE (a) Data acquisition system (b) Machine structure (Tribology lab, FKM, UTeM)	66
3.11	Digital photograph of Carl Zeiss Axioskop 2 MAT optical microscopy (Material lab, FKP, UTeM)	71
3.12	Digital photograph of Zeiss EVO 50 scanning electron microscope (Material lab, FKP, UTeM)	72

3.13	Digital photograph of JEOL field emission scanning electron microscope, model: JSM-6700F (Biomedical engineering research group (BERG), faculty of engineering, UIAM)	73
4.1	FESEM micrograph of as-received magnesium powder (a) at $100 \times$ magnification (b) at $200 \times$ magnification	75
4.2	Particle size distribution graphs of as-received magnesium powder	75
4.3	FESEM micrograph of as-received silicon carbide powder (a) at $100 \times$ magnification (b) at $400 \times$ magnification	76
4.4	Particle size distribution graphs of as-received silicon carbide powder	76
4.5	FESEM micrographs of as-received multi-walled carbon nanotubes (a) at $30,000 \times$ magnification (b) at $60,000 \times$ magnification	77
4.6	(a) Sintered billet (b) Extruded rod	78
4.7	SEM micrographs of extruded composites (a) Mg/SiC (b) Mg/SiC/MWCNTs at $150 \times$ magnification	79
4.8	FESEM micrographs of extruded hybrid composites Mg/SiC/MWCNTs (a) at $37,000 \times$ magnification (b) at $100,000 \times$ magnification	80
4.9	Etched SEM micrographs of extruded (a) Pure Mg (b) Composites Mg/SiC (c) Composites Mg/SiC/MWCNTs at $1000 \times$ Magnification	81
4.10	Comparisons of theoretical density and experimental density for different samples	83
4.11	Comparisons of calculated volumetric porosity for different	84

	samples	
4.12	Variation of Hardness Number (HV) measured for different samples	86
4.13	Comparative graphs of wear rate (mm^3/m) with (a) Sliding speed : 0.5 m/s; (b) Sliding speed : 1.5 m/s; (c) Sliding speed : 3.5 m/s; (d) Sliding speed : 4.5 m/s as a function of various applied load of different samples corresponding to sliding distance of 5000 m	89
4.14	Comparative graphs of wear rate (mm^3/m) with (a) Load : 5 N; (b) Load : 10 N; (c) Load : 20 N; (d) Load : 40 N as a function of various sliding speed of different samples corresponding to sliding distance of 5000 m	90
4.15	Variation of coefficient of friction (μ) with (a) Load : 5 N; (b) Load : 10 N; (c) Load : 20 N; (d) Load : 40 N as a function of various sliding speed of different samples corresponding to sliding distance of 5000 m	92
4.16	SEM images of worn surface at sliding speed of 1.5 m/s (a) Mg, (b) Mg/SiC, (c) Mg/SiC/MWCNTs under load of 5 N, (d) Mg, (e) Mg/SiC, (f) Mg/SiC/MWCNTs under load of 10 N, (g) Mg, (h) Mg/SiC, (i) Mg/SiC/MWCNTs under load of 20 N, (j) Mg, (k) Mg/SiC, (l) Mg/SiC/MWCNTs under load of 40 N at $150 \times$ magnification	95
4.17	SEM images of worn surface at load of 20 N (a) Mg, (b) Mg/SiC, (c) Mg/SiC/MWCNTs under sliding speed of 0.5 m/s , (d) Mg, (e) Mg/SiC, (f) Mg/SiC/MWCNTs under sliding speed of 1.5 m/s , (g)	96

	Mg, (h) Mg/SiC, (i) Mg/SiC/MWCNTs under sliding speed of 3.5 m/s , (j) Mg, (k) Mg/SiC, (l) Mg/SiC/MWCNTs under sliding speed of 4.5 m/s at 150 × magnification	
4.18	(a) Ribbon-Like Strips from Mg Specimen Tested Under Load of 40 N and Sliding Speed of 1.5 m/s (b) Corresponding EDX spectra for Figure 4.18a	97
4.19	Large amount of transferred material covering the worn surface of Mg/SiC/MWCNTs test under load of 10 N and sliding speed of 1.5 m/s (a) at 150 × magnification (b) at 900 × magnification (c) corresponding EDX spectra for Figure 4.19b	98
4.20	(a) Fine Oxide Debris from Mg/SiC/MWCNTs Specimen Tested Under Load of 10 N and Sliding Speed of 1.5 m/s (b) Corresponding EDX spectra for Figure 4.20a	99
4.21	Worn surface of Mg/SiC/MWCNTs test under load of 20 N and sliding speed of 4.5 m/s (a) at 150 × magnification (b) corresponding EDX spectra for Figure 4.21a	109
4.22	(a) Cracks running perpendicular to the sliding direction indicative of delamination (b) Large craters formed due to the material removed from pin surface during delamination	110
4.23	(a) Wear debris showing flake type particles (b) EDX analysis showing the presence of oxygen in delamination wear debris.	111
4.24	SEM images of worn surface (a) Mg, (b) Mg/SiC, (c) Mg/SiC/MWCNTs at 150 × magnification, (d) Mg, (e) Mg/SiC, (f) Mg/SiC/MWCNTs at 900 × magnification under load of 40 N and	112

	sliding speed of 3.5 m/s, Corresponding EDX Spectra (g) from Figure d, (h) from Figure e, (i) from Figure f.	
4.25	FESEM images of worn surface Mg/SiC/MWCNTs under (a) Load of 40 N and sliding speed of 1.5 m/s (b) Load of 40 N and sliding speed of 4.5 m/s at $55000 \times$ magnification	114
4.26	(a) Featureless worn surface of Mg/SiC/MWCNTs test under load of 40N and sliding speed of 4.5m/s at $150 \times$ magnification (b) surface pin material extruded to trailing edge and re-solidified around the periphery during sliding (c) Large, irregular lumps in the wear debris	115
4.27	(a) Cross-section of worn surface Mg/SiC/MWCNTs parallel to the sliding direction under load of 40 N and sliding speed of 3.5 m/s at $300 \times$ magnification (b) Corresponding EDX spectra of Figure 4.27a	116
4.28	Wear mechanism map of the studied composites with a approximate boundaries of dominant wear mechanisms at the different sliding conditions	117

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	A list of equipments / Instruments used	135
B	A list of chemical used	139
C1	The details drawing of compaction die	140
C2	The details drawing of compaction punch	141
C3	The details drawing of stopper	142
D1	The details drawing of extrusion die	143
D2	The details drawing of extrusion plunger	144
D3	The details drawing of holder for extrusion die	145
E	Chemical analysis of the counterbody	146

LIST OF ABBREVIATIONS

ASTM	American society for testing materials
Al	Aluminium
Al ₂ O ₃	Alumina
AlN	Aluminum nitride
AE42	Magnesium alloy with about 4 wt.% Al and 2 wt.% about mischmetal
AM60B	Magnesium alloy with about 6 wt.% Al and less than 1 wt.% Mn
AZ91D	Magnesium alloy with about 9 wt.% Al and about 1 wt.% Zn
B ₄ C	Boron carbide
BCC	Body centered cubic
BN	Boron nitride
BPR	Ball to powder ratio
C	Carbon
CFMMCs	Continuous fiber reinforced metal matrix composites
CMCs	Ceramic matrix composites
CNT	Carbon nanotube
CO ₂	Carbon dioxide
CTE	Coefficient of thermal expansion
Cu	Copper

DMD	Disintegrated melt deposition
EDX	Energy dispersive X-ray spectrometer
FCC	Face centered cubic
FEG	Field Emission Gun
FESEM	Field emission scanning electron microscopy
Grp	Graphite
HCP	Hexagonal close packed
Hv	Vickers hardness number
Mg	Magnesium
Mg/SiC	Magnesium reinforced with silicon carbide
Mg/SiC/MWCNTs	Magnesium reinforced with silicon carbide and multi-wall carbon nanotubes
Mg ₂ Si	Magnesium silicide
MgO	Magnesium oxide
MM	Mechanical milling
MMCs	Metal matrix composites
Mn	Manganese
MSDS	Material safety data sheet
Ni	Nickel
OM	Optical microscopy
PCA	Process control agent
PM	Powder metallurgy
PMCs	Polymer matrix composites
PRMMCs	Particulate reinforced metal matrix composites

PSA	Particle size analyzer
QE22	Magnesium alloy with 2.5% Ag, 2% RE and 0.7% Zr
RE	Rare earth metals
SEI	Secondary electron imaging
SEM	Scanning electron microscopy
SiC	Silicon carbide
SiO ₂	Silica
Ti	Titanium
TiB ₂	Titanium diboride
TiC	Titanium carbide
W	Tungsten
XRD	X-ray diffraction
Y ₂ O ₃	Yttrium(III) oxide
Zn	Zinc
Zr	Zirconium